



JME SERIES

JME Indoor/Outdoor enclosure box is designed to be assembled into the distributing box with various control functions according to the type of components, Specification and quantity.

The Structure is so light that can be very perfect. It's made of cold-rolled Steel board or stainless steel alloy. We can provide a wide range of cabinets for your reference.

FEATURES

- ✓ Body and door manufactured in 1.2/1.5 mm sheet steel.
- ✓ mounting plate with folded edge in 2.0mm sheet steel.
- ✓ Finished with thermosetting epoxy polyester powder coating body and door textured finish protection degree.
- ✓ IP 55/65 protection degree boxes are complete with:
- ✓ 2 zinc passivated rails to be fixed on the door .
mounting Plate
- ✓ Gland Plate and gasket.
- ✓ Package with hardware for earth connection and screws to mount all components

GLAND BOX

MODEL	External Size: (mm)			No. of Lock	Gland Opening	Mounting Plate	
	H	W	D			I	G
JME2 215	202	200	150	1	O	165	150
JME2 215	250	200	150	1	O	215	150
JME25 215	250	250	150	1	A	215	200
JME2 315	300	200	150	1	O	205	150
JME25 315	300	250	150	1	A	265	200
JME3 315	300	300	150	1	B	265	250
JME4 315	300	400	150			265	350
JME3 415	400	300	150	1	B	365	250
JME4 415	400	400	150	1	B	365	350
JME3 515	500	300	150	1	B	465	250
JME4 515	500	400	150	1	C	465	350
JME5 515	500	500	150	1	D	465	450
JME4 615	600	400	150	2	C	565	350
JME5 615	600	500	150	2	D	565	450
JME25 320	300	250	200	1	A	265	200
JME3 320	300	300	200	1	B	265	250
JME4 320	300	400	200	1	B	265	350
JME3 420	400	300	200	1	B	365	200
JME4 420	400	400	200	1	B	365	350
JME6 420	400	600	200	1	D	365	550
JME3 520	500	300	200	1	B	465	250
JME4 520	500	400	200	1	B	465	350
JME5 520	500	500	200	1	D	465	450
JME4 620	600	400	200	2	C	565	350
JME5 620	600	500	200	2	D	565	450
JME6 620	600	600	200	2	D	565	550
JME5 720	700	500	200	2	D	665	450
JME6 720	700	600	200	2	D	665	550
JME6 820	800	600	200	2	D	765	550
JME8 820	800	800	200	2	E	765	700
JME6 1020	1000	600	200	2	D	965	550
JME8 1020	1100	800	200	2	E	965	750
JME6 1220	1200	600	200	2	D	1165	550
JME8 1220	1200	800	200	2	E	1166	750
JME4 425	400	400	250	1	C	365	350
JME6 425	400	600	250	1	D	365	550
JME4 525	500	400	250	1	C	465	350
JME5 525	500	500	250	1	D	465	450
JME4 625	600	400	250	2	C	565	350
JME5 625	600	500	250	2	D	565	450
JME6 625	600	600	250	2	D	565	550
JME5 725	700	500	250	2	D	665	450
JME6 825	800	600	250	2	D	765	550
JME8 825	800	800	250	2	E	765	700
JME6 1025	1000	600	250	2	D	965	550
JME8 1025	1000	800	250	2	E	965	750
JME6 1225	1200	600	250	2	D	1165	550
JME8 1225	1200	800	250	2	E	1165	750
JME6 430	400	600	300	1	D	365	550
JME4 530	500	400	300	1	C	465	350
JME4 630	600	400	300	2	C	565	350
JME5 630	600	500	300	2	D	565	450
JME6 630	600	600	300	2	D	565	550
JME5 730	700	500	300	2	D	665	450
JME6 830	800	600	300	2	D	765	550
JME8 830	800	800	300	2	E	765	750
JME6 1030	1000	600	300	2	D	965	550
JME6 1230	1200	600	300	2	D	1165	550
JME8 1030	1000	800	300	2	E	965	750
JME8 1230	1200	600	300	2	E	1165	750
JME8 1430	1400	800	300	3	E	1365	750
JME6 840	800	600	400	2	D	765	550
JME8 840	800	800	400	2	E	765	750
JME6 1040	1000	600	400	2	D	965	550
JME8 1040	1000	800	400	2	E	965	750
JME6 1240	1200	600	400	2	D	1165	550
JME8 1240	1200	800	400	2	E	1165	750
JME8 1440	1400	800	400	2	E	1365	750

MODEL	Size (mm)		
	W	H	D
JGB 432	400	300	200
GB 532	500	300	200
JGB 632	600	300	200
GB 8325	800	300	250
JGB 4252	400	250	200
JGB 5252	500	250	200
JGB 6252	600	250	200
JGB 82525	800	250	250
JGB 422	400	250	200
JGB 422	500	200	200
JGB 1033	1,000	300	300

